

CENTOPLEX CX 4 375 AU

High-speed grease for gears



Benefits for your application

- For small gears subject to high peripheral speeds
- Shear stable
- Good oil separation at low temperatures

Description

CENTOPLEX CX 4/375 AU is a special lubricating grease based on mineral oil and lithium soap. It is a very soft grease of consistency grade 0.

Application

Being a grease of very low consistency CENTOPLEX CX 4/375 AU is suitable for small gears subject to high speeds, especially bevel gears in right angle grinders. At temperatures < 80°C long-term lubrication is possible.

Application notes

CENTOPLEX CX 4/375 AU can be applied onto the tooth flanks by brush in order to allow minimum quantity lubrication. Lubrication is also possible by providing a grease sump in the gear. Due to the good oil separation, wetting of the lubrication points in gears or bearings is ensured. CENTOPLEX CX 4/375 AU can also be applied through central automatic lubrication systems.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	CENTOPLEX CX 4/375 AU
Can 1 kg	+
Bucket 25 kg	+

Product data	CENTOPLEX CX 4/375 AU
Article number	020047
Chemical composition, type of oil	mineral oil
Chemical composition, thickener	lithium soap
Lower service temperature	-30 °C / -22 °F
Upper service temperature	120 °C / 248 °F
Colour space	brown
Appearance	almost transparent
Texture	homogeneous
Worked penetration, DIN ISO 2137, 25 °C, lower limit value	355 x 0.1 mm
Worked penetration, DIN ISO 2137, 25 °C, upper limit value	385 x 0.1 mm
Corrosion inhibiting properties of lubricating greases, DIN 51802, (SKF-EMCOR), test duration: 1 week, distilled water	<= 1 corrosion degree
Oil separation, DIN 51817 N, after 7 d/40 °C	<= 7 % by weight



CENTOPLEX CX 4 375 AU

High-speed grease for gears

Product data	CENTOPLEX CX 4/375 AU
Flow pressure of lubricating greases, DIN 51805-2, test temperature: -30 °C	<= 1 400 mbar
Drop point, DIN ISO 2176, IP 396	>= 150 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.